


# DS-2CE16A2P(N)-IT3

## 700TVL DIS EXIR Bullet Camera




**EXIR**



### Key features

- 700 TVL Horizontal Resolution
- True Day/Night
- 2.8/3.6/6/8/12/16mm Fixed Lens, 0.1 lux /F1.2
- 40m IR Distance
- Wide Operating Temperature Range:  
-40°C to 60°C (-40°F to +140°F)

### Dimensions



DS-2CE16A2P(N)-IT3	
<b>Camera</b>	
Image Sensor	1/3" DIS
Signal System	PAL/NTSC
Effective Pixels	976 (H) x 496 (V)
Min. Illumination	0.1 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter speed	PAL: 1/50 s to 1/100,000 s NTSC: 1/60 s to 1/100,000 s
Lens	3.6mm (2.8mm,6mm,8mm,12mm,16mm optional)
	Angle of view: 68.4° (3.6 mm)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
Horizontal Resolution	700 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
<b>General</b>	
Working Temperature/Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC
Power Consumption	Max. 5 W
Ingress Protection	IP66
IR Range	40 meters
Dimensions	94.6x83x210.8mm(3.72"x3.27"x8.30")
Weight	700 g (1.54 lbs)

### Available models

PAL: DS-2CE16A2P-IT3  
NTSC: DS-2CE16A2N-IT3